



THE FINISHING TOUCH

METRO + GEO
BATH ACCESSORIES

INSTALLATION, USE & CARE INSTRUCTIONS

*Thank you for your purchase, please enjoy your new Bath Accessory. They complement any ceramic, porcelain, metal or stone tile. Surface markings and natural color variations are inherent qualities of Questech Cast Stone, Cast Metal and Natural Stone; adding to the beauty of all Questech products. **Please inspect your product prior to installation.***

QUESTECH TILE WARRANTY

The Questech limited warranty for Questech Cast Stone Tile, Questech Cast Metal Tile, and Questech Natural Stone Tile can be found at: www.Questech.com/Warranty

Q-SEAL™ PERMANENT PROTECTION

Accessory surfaces are protected by Q-Seal, a permanent sealer that is water and stain resistant, protects against abrasion, and inhibits the growth of stain and odor-causing mold and mildew. Q-Seal is factory-applied and never needs re-sealing.

Q-SEAL WARRANTY

Q-Seal is guaranteed to be water and stain resistant for as long as you own your home. For complete warranty information please visit: www.Questech.com/Warranty

INSTALLATION INSTRUCTIONS

- Following the adhesive manufacturer's instructions.
- Set wall tile to height accessory will be located.
- Trowel a layer of adhesive on the dove-tails (teeth) of each accessory prior to placing on the combed adhesive bed to obtain 100% coverage.
- Dove-tail should be pushed into adhesive to ensure good contact. The accessory's back should overlap the wall tile.
- Continue wall installation around the accessory, noting that the accessory's back should overlap the wall tile.
- Tape accessory in place until adhesive bonds.
- Do NOT beat in with the butt-end of the trowel.

CARE AND MAINTENANCE

- To clean, use any ordinary household cleaner. For best results, we recommend a liquid, non-abrasive cleaner.
- Liquid abrasive household cleaners should only be used after being tested in a small inconspicuous area to ensure that no damage will result.
- Do NOT clean with scouring pads, steel wool, or other abrasive implements or damage to the surface may result.
- Cleaners containing ammonia, bleach or other harsh chemicals should be wiped up shortly after application or damage to the surface may result.

SETTING MATERIALS

Select one of the following two adhesives:

- Thin-Set: A liquid latex (polymer) fortified premium thin-set Portland cement mortar conforming to ANSIA118.4.
- Epoxy: A water-cleanable epoxy mortar conforming to ANSIA118.3.

